




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04Q 7/34</b>		A1	(11) International Publication Number: <b>WO 96/14720</b>
			(43) International Publication Date: 17 May 1996 (17.05.96)
(21) International Application Number: <b>PCT/FI95/00606</b> (22) International Filing Date: <b>6 November 1995 (06.11.95)</b> (30) Priority Data: <b>945223</b> <b>7 November 1994 (07.11.94)</b> <b>FI</b> (71) Applicant (for all designated States except US): <b>NOKIA TELECOMMUNICATIONS OY [FI/FI]; Mäkkylän puistotie 1, FIN-02600 Espoo (FI).</b> (72) Inventor; and (75) Inventor/Applicant (for US only): <b>KOIVU, Vesa [FI/FI]; Rantakoivuntie 14, FIN-90630 Oulu (FI).</b> (74) Agent: <b>OY KOLSTER AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).</b>		(81) Designated States: <b>AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).</b> Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Finnish).	

(54) Title: CELLULAR RADIO SYSTEM AND A BASE STATION



## (57) Abstract

The present invention relates to a cellular radio system comprising a base station controller (BSC) and base stations (BTS) connected to it. For an easy and reliable configuring of the base stations of the system, the system comprises at least two base stations (BTS) which are arranged to transmit a base station specific identification message to the base station controller (BSC) by utilizing the same predetermined communication channel (CH1) during initialization, whereby the base station controller (BSC) comprises means (1, 2, 3) for assigning a predetermined base station specific communication channel (CH5) to a base station by utilizing said predetermined communication channel (CH1) in response to receiving the identification message. The invention further relates to a base station.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## Cellular radio system and a base station

5       The present invention relates to a cellular radio system comprising a base station controller and base stations connected to it. The invention further relates to a base station of a cellular radio system, comprising transmission units for transmitting communication signals to the base station controller and for receiving communication signals from the base station controller on  
10       a communication link, whereby the transmission units are arranged to feed a base station specific identification message to the base station controller by utilizing a predetermined communication channel in response to the base station initialization.

15       The term initialization in this context refers to a procedure carried out, for example, when the supply power is for the first time connected to the base station, after which the base station carries out initial functions programmed for it.

20       The invention relates to a communication network of a cellular radio system, such as the GSM (Groupe Spécial Mobile) or DCS (Digital Cellular System), and particularly to the communication link between base stations and the base station controller. The prior art technology  
25       recognizes cellular radio systems in which all base stations connected to the same communication link (a chain or a ring network), such as a 2 Mbit/s PCM connection, are assigned a dedicated, base station specific communication channel, i.e. a PCM (Pulse Code Modulation) time slot,  
30       which is utilized by the base stations as they for the first time establish a connection to the base station controller. This means that the base stations, in connection with the initialization following the installation, for example, from the very beginning  
35       establish contact to the base station controller on a base

station specific O&M channel (Operation & Maintenance) assigned to them. In order for this to be possible, the person who installs the base station must, at the installation stage, feed data concerning the channel configuration of the system to the base station. In practice, this takes place so that the base station installer, during the installing, connects a portable microcomputer or a service terminal specifically intended for the initialization of transmission units to the base station, by means of which service terminal he feeds transmission branching tables of the system to the base station, indicating, among other things, which PCM time slots are allocated for use by the base station in question, and which PCM time slots the base station should repeat forward in the network.

The most serious weakness of the above-mentioned prior art solution is the difficulty concerning its application. In order for the installer to be able to feed the base station with correct data, he must have a considerable amount of information on the channel allocation of the network. In addition, it is difficult to correct any errors that may occur in the feeding process, because that would require another visit by the installer to the base station site (errors, if any, are usually detected only afterwards). If the configuring of a base station fails, for example, in connection with a reconfiguration of the network during, e.g., channel re-allocation, the installer must visit the base station site to feed the base station with the new data by means of the service terminal.

It is an object of the present invention to solve the aforementioned problems and to provide a cellular radio system in which the configuring of base stations is considerably simpler than in the prior art solutions. This object is achieved by a cellular radio system according to

the invention, characterized in that the system comprises at least two base stations which are arranged to transmit a base station specific identification message to the base station controller by utilizing the same predetermined communication channel during their initialization, and that the base station controller comprises means for assigning a predetermined base station specific communication channel to a base station by utilizing said predetermined communication channel in response to receiving the identification message.

The invention further relates to a base station which can be utilized in the system according to the invention. The base station according to the invention is characterized in that the base station is arranged to receive a message from the base station controller on said predetermined communication channel, and to adjust the transmission units onto a communication channel assigned by said message (S1).

The invention is based on the idea that when a common communication channel is reserved for the base stations in the system, and the base stations are arranged to utilize said common channel when they for the first time contact the base station controller, it is possible to carry out the configuring of the transmission units of the base stations so that the base station controller feeds data concerning the network configuration to the base stations by using said common channel, i.e. assigns each base station a dedicated communication channel. Therefore, it is unnecessary to carry out the configuring of the transmission units of the base stations at the installation site during the installing of the base station, but it can be performed by remote control from the network management center. Thus, the most significant advantages of the system and base station according to the invention are the facts that it is considerably faster and

easier to carry out the configuring of the transmission units of the base stations during the installing; that the configuring of the base stations can be carried out in a centralized manner whereby the error possibility decreases; that the correcting of errors which may have occurred during the configuring or reconfiguring of the base station no longer requires a visit by the installer to the base station; and that the channel configuration of the network does not have to be finally determined when the base station or stations are being installed, because its/their transmission units can be configured afterwards.

The preferred embodiments of the system and base station according to the invention are disclosed in the attached dependent claims 2 - 3 and 5 - 6. In the following, the invention will be described in closer detail by means of a preferred embodiment according to the invention with reference to the attached drawings, in which

figure 1 is a block diagram illustration of a cellular radio system according to the invention, and figure 2 illustrates a detail of the system shown in figure 1.

Figure 1 is a block diagram illustration of a preferred embodiment of a cellular radio system according to the invention. The block diagram of figure 1 shows a part of a GSM (Groupe Spécial Mobile) communication network.

The base station controller BSC of figure 1 communicates with the mobile services switching center (not shown in the figure) of the network in order to forward calls between the mobile services switching center and the base stations BTS. Base stations are connected to the base station controller by means of three 2 Mbit/s PCM branches 4 (Pulse Code Modulation) whereby, in connection with the network configuring, a certain number of time

slots are allocated in a PCM connection for each base station. The data concerning the channel configuration of the network, i.e. the transmission branching tables of the base stations, are stored in the memory 2 of the base station controller. It is possible for the operator to edit the data stored in the memory 2 by remote control from his control room.

In the case of figure 1, a common channel consisting of one or more time slots of the PCM connection, or parts of it, has been allocated in each of the three PCM connections 4 to be commonly used by each base station connected to it. Thus, said channel may consist of one PCM time slot (64 kbit/s) or, for example, 1/4 of a PCM time slot (16 kbit/s), or alternatively of more PCM time slots ( $n \times 64$  kbit/s). As the common channel of the base stations, it is possible to use the same channel in all three branches 4, or alternatively a different channel may be used in each branch, depending on the case. The transmission units of all the base stations BTS connected to a certain branch 4 have been adjusted in connection with the assembly so that the base stations, in connection with the initialization, transmit a predetermined identification message (cf. figure 2) to the base station controller by utilizing the common channel of the branch. If the common channel for a reason or another is busy, the base station waits on for a while, and then repeats the attempt until it succeeds in transmitting the identification message.

Each PCM branch 4 is connected to the base station by a cross connector 3. The cross connectors 3 are adjusted so that they monitor the messages transmitted on the common channel of the branch 4 in question. As an identification message on the common channel of the branch 4 in question is detected by any one of the cross connectors 3, it forwards said message to a transmission

control 1 of the base station controller. The transmission control 1 may be common for all the PCM branches 4, as in figure 1, or alternatively it is possible to arrange to the base station controller a dedicated transmission control for each PCM branch 4.

Upon receiving an identification message from a base station BTS, the transmission control 1 searches a transmission table stored in the memory 2 for said base station, and transmits it to the base station by utilizing the same common transmitting channel on which the base station BTS initially contacted the base station controller BSC. When the base station BTS that transmitted the identification message receives the data transmitted by the base station, it breaks the connection to the base station controller, after which it adjusts its transmission unit on the basis of the data it received, whereby it discontinues utilizing the common channel and moves to use the base station specific O&M channel assigned to it by means of the transmission branching table. The aforementioned procedures (utilization of the common channel, etc.) are repeated if the base station is re-initialized, for example, by remote control from the system control center.

Figure 2 illustrates a detail of the system shown in figure 1. Figure 2 illustrates signalling between a base station BTS and a base station controller BSC in connection with the base station BTS initialization.

In connection with the assembly of the base station or, alternatively, its installation, the installer determines an identifier for the base station by means of a DIP switch 5. The transmission units 7 of the base station BTS are arranged to check the position of the DIP switch, i.e. to read the base station identifier from it in connection with their initialization. Following this, the transmission units of the base station BTS include the



identifier into the identification message S1 to be sent to the base station controller. Said message is transmitted on the common channel CH1 which has been allocated in the PCM connection 4, and onto which the transmission units have been adjusted during assembly.

Having transmitted the identification message S1, the transmission units shift to wait state where they monitor the common channel CH1 in order to detect the message S2 transmitted from the base station. Upon detecting said message, the transmission units begin receiving it and storing the data which are contained in the message to a memory 6. Thus, it is possible to store in the memory 6 the transmission branching table of the base station in question, which table indicates, among other things, which PCM time slots are allocated for use by the base station BTS in question, and which PCM time slots (channels) the transmission units of the base station should repeat forward in the network.

As soon as the message S2 transmitted by the base station is received in full, the base station BTS discontinues using the common channel CH1 by breaking the connection to the base station controller, and adjusts its transmission units on the basis of the data stored in the memory 6. Following this, the base station transmits a new message S3 to the base station controller BSC by using a base station specific O&M channel CH5 assigned to it.

It should be noted that the description above and the figures relating to it are only intended to illustrate the present invention. Different kinds of variations and modifications of the present invention will become obvious for a person skilled in the art, without departing from the scope and spirit of the invention disclosed in the attached claims.

## Claims

1. A cellular radio system comprising a base station controller (BSC) and base stations (BTS) connected to it, characterized in that the system comprises at least two base stations (BTS) which are arranged to transmit a base station specific identification message (S1) to the base station controller (BSC) by utilizing the same predetermined communication channel (CH1) during their initialization, and that the base station controller (BSC) comprises means (1, 2, 3) for assigning a predetermined base station specific communication channel (CH5) to a base station by utilizing said predetermined communication channel (CH1) in response to receiving the identification message (S1).

2. A system as claimed in claim 1, characterized in that the base station controller (BSC) comprises a memory means (2) for receiving and storing base station specific data fed by an operator, and means (1, 2) for feeding said data from the memory means to the base station (BTS) by utilizing said predetermined communication channel (CH1) in response to the identification message (S1).

3. A system as claimed in claim 1, characterized in that the base stations (BTS) are connected to the base station controller (BSC) by a PCM connection (4), whereby said predetermined communication channel (S1) consists of one or more time slots of the PCM connection, or parts of a time slot.

4. A base station (BTS) of a cellular radio system, comprising transmission units (7) for transmitting communication signals (S1, S3) to the base station controller and for receiving communication signals (S2) from the base station controller on a communication link (4), whereby the transmission units (7) are arranged to

feed a base station specific identification message (S1) to the base station controller by utilizing a predetermined communication channel (CH1) in response to the base station (BTS) initialization, characterized in that the base station is arranged to receive a message (S2) from the base station controller (BSC) on said predetermined communication channel (S1), and to adjust the transmission units (7) onto a communication channel (CH5) assigned by said message (S1).

5. A base station as claimed in claim 4, characterized in that said communication link (4) is a PCM connection, whereby said predetermined communication channel (CH1) consists of one or more time slots of the PCM connection, or parts of a time slot.

6. A base station as claimed in claim 4, characterized in that the base station (BTS) comprises manually adjustable switching means (5) for feeding an identifier to the base station (BTS), whereby the transmission units (7) are arranged to transmit an identification message being responsive to the position of said switching means (5) to the base station controller (BSC) in response to the initialization of the base station (BTS).

7. A base station as claimed in claim 4, characterized in that the base station comprises a memory means (6) for storing the data contained in the message (S2) received from the base station controller, and means for adjusting the transmission units (7) on the basis of the data stored in said memory means.




FIG. 1




FIG. 2

1  
INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 95/00606

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC6: H04Q 7/34

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04Q, H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0534612 A2 (MOTOROLA, INC.), 31 March 1996 (31.03.96), column 4, line 56 - column 5, line 16; column 5, line 54 - column 6, line 42 --	1-7
Y	US 5297193 A (BOUIX ET AL), 22 March 1994 (22.03.94), column 1, line 55 - line 68; column 2, line 16 - column 3, line 45; column 7, line 18 - line 31, column 7 line 39 - 53 -----	1-7

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

- \* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \* "&" document member of the same patent family

Date of the actual completion of the international search

9 April 1996

Date of mailing of the international search report

10 -04- 1996

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Peter Hedman  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

05/02/96

International application No.  
PCT/FI 95/00606

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A2- 0534612	31/03/96	AU-B- 638379	24/06/93
		AU-A- 1842792	04/03/93
		CN-A- 1070074	17/03/93
US-A- 5297193	22/03/94	AT-T- 120601	15/04/95
		CA-A- 2043291	01/12/91
		DE-D,T- 69108450	27/07/95
		EP-A,B- 0460486	11/12/91
		SE-T3- 0460486	
		ES-T- 2071160	16/06/95
		FR-A,B- 2662879	06/12/91
		NO-B- 178598	15/01/96